

SCUBA Cylinders - Aluminium

Specifications - 6061 Aluminium

Water Capacity	Diameter	Length	Weight	Charging Pressure	Test Pressure	Thread	Specification
litres	mm	mm	kg	bar	bar		
0.35	60	250	0.93	300	450	M18 x 1.5 ISO	PED
0.4	60	255	0.7	232	348	M18 x 1.5 ISO CP	PED
0.5	68	245	0.87	200	300	M18 x 1.5 ISO CP	PED
0.5	68	285	2.95	300	450	M18 x 1.5 ISO CP	PED
1	102	240	1.5	200	300	M18 x 1.5 ISO CP	PED
1.5	111	295	2.7	232	348	M25 x 2 ISO CP 10	PED
1.5	111	295	2.7	232	348	M18 x 1.5 ISO CP	PED
3	111	515	4.5	232	348	M25 x 2 ISO CP 10	PED
3.8	140	420	5.5	200	300	M25 x 2 ISO CP 10	PED
4.4	152	420	6.5	200	300	M25 x 2 ISO CP 10	PED
7	152	620	9.8	232	348	M25 x 2 ISO CP 10	PED
7	176	500	11.1	232	359	M25 x 2 ISO CP 10	PED
7	152	610	8.61	200	300	M25 x 2 ISO CP 10	PED
10	176	655	12.4	200	300	M25 x 2 ISO CP 10	PED
10	176	655	12.4	200	300	M25 x 2 DIN 477	PED
10.4	204	560	16.1	232	348	M25 x 2 ISO CP 10	PED
12	204	610	16.5	200	300	M25 x 2 DIN 477	PED
12	204	612	16.5	200	300	M25 x 2 ISO CP 10	PED
12.2	204	635	18.1	232	348	M25 x 2 ISO CP 10	PED

Colwick, Nottingham, NG4 2BH, England.
Tel: +44 (0)115 980 3800 Fax: +44 (0)115 980 3899

© 2003 Luxfer Inc.