

ALUMINUM

Material
Alloy aluminum high-resistance

Certification



Model	Liters	CODES	Bar	Valve	Diameter	Height*	Weight*	Buoyancy with full cylinder	Buoyancy with 35 bar remaining	Buoyancy with empty cylinder
S80	11.1	TK700111/PED	200	Single valve Coltri 25x2	18,42 cm	65,8 cm	14,2 Kg	- 0,72 Kg	+ 1,27 Kg	+ 1,85 Kg
		TK700112	200	Double valve 2-2000	18,42 cm	65,8 cm	14,2 Kg	- 0,72 Kg	+ 1,27 Kg	+ 1,85 Kg
S53	7.6	TK700117	200	Single valve Coltri 25x2	18,42 cm	48,8 cm	11,4 Kg	- 3,8 Kg	- 0,8 Kg	+ 0,1 Kg
		TK700118	200	Double valve 2-2000	18,42 cm	48,8 cm	11,4 Kg	- 3,8 Kg	- 0,8 Kg	+ 0,1 Kg
S40	5.8	TK700113/PED	200	Single valve Coltri 25x2	13,34 cm	63,5 cm	7,3 Kg	- 0,68 Kg	+ 0,31 Kg	+ 0,63 Kg

* Indicative without valve

